

ENDURO 4T RACING SAE 10W-40

ENDURO 4T RACING SAE 10W-40 is a high quality four stroke motorcycle multigrade lubricant oil formulated from synthetic base oil and selective API SL additives.

ENDURO 4T RACING SAE 10W-40 has passed the variable speed friction test with high result over high friction reference oil to assure that no wet clutch slippage on it's field application.

ENDURO 4T RACING SAE 10W-40 là dầu đa cấp bôi trơn động cơ bốn thì chất lượng cao có công thức từ dầu gốc tổng hợp và hệ phụ gia lựa chọn đáp ứng API SL.

ENDURO 4T RACING SAE 10W-40 đạt kết quả cao trong thử nghiệm ma sát với tốc độ biến thiên so với dầu đối chứng, điều này đảm bảo không có sự trượt ly hợp ướt trong điều kiện sử dụng.

Các chỉ tiêu	Phương Pháp	ENDURO 4T RACING SAE 10W-40
Độ nhớt SAE		10W-40
Tỷ trọng ở 15 ⁰ C, kg/l	ASTM D – 4052	0.8741
Độ nhớt động học ở:		
40 ⁰ C, cSt	ASTM D - 445	104.9
100 ⁰ C, cSt	ASTM D - 445	15.69
Chỉ số độ nhớt (VI)	ASTM D - 2270	159
Màu ASTM	Cảm quan	Xanh đậm
Điểm chớp cháy, ⁰ C	ASTM D - 92	224
Điểm rót chảy, ⁰ C	ASTM D - 5950	-30
Trị số kiềm tổng (TBN), mgKOH/g	ASTM D – 2896	9.56

PERFORMANCE LEVELS

ENDURO 4T RACING SAE 10W-40 meets JASO MA2 specification and API SL/SJ.

SUPERIOTIES

- Prevents wet clutch slippage.
- Stable viscosity at low and high temperatures
- SAE 10W-30 viscosity, suitable for new generation motorcycle and high acceleration.
- Excellent oxidation and degradation stability under exposure to high operating temperature.
- Keeps engine clean and provides excellent protection against piston deposit formation, rust and keep engine parts from wear.

APPLICATION

ENDURO 4T RACING SAE 10W-40 is recommended for four stroke motor engines such as Yamaha, Honda, Suzuki, Kawasaki, and other motorcycle. This oil also suitable for four stroke motor engine made in China and Korea.

MỨC CHẤT LƯỢNG

ENDURO 4T RACING SAE 10W-40 đáp ứng tiêu chuẩn JASO MA2 và API SL/SJ.

ƯU ĐIỂM

- Ngăn chặn trượt ly hợp ướt.
- Ổn định độ nhớt ở nhiệt độ thấp và cao.
- Độ nhớt SAE 10W-40 phù hợp cho xe máy thể hệ mới và tốc độ cao.
- Ổn định oxi hóa tuyệt vời và hạn chế giảm chất lượng dưới điều kiện nhiệt độ hoạt động cao.
- Giữ động cơ sạch sẽ và cung cấp bảo vệ tuyệt vời chống lại hình thành cặn piston, gỉ và giữ các bộ phận động cơ khỏi mài mòn.

ỨNG DỤNG

ENDURO 4T RACING SAE 10W-40 được khuyến nghị cho động cơ xe máy bốn thì như Yamaha, Honda, Suzuki, Kanzen và xe máy khác. Dầu này cũng thích hợp cho động cơ bốn thì sản xuất tại Trung Quốc và Hàn Quốc.